


OLIATORI A LIVELLO COSTANTE CONSTANT LEVEL OILERS

Art. 705

Oliatore a livello costante corpo in alluminio e vaso in materiale plastico.
Constant level oiler with aluminium body and plastic material bottle.

Ø vaso mm Ø bottle mm	capacità ml. capacity ml.	h. tot. mm h. tot. mm
57	115	87



Attacco: G1/4
Connection: BSP 1/4
Temperatura max. 65° C
Max. temperature 65° C
Peso Kg. 0,155
Weight Kg. 0,155



Art. 710

Oliatore a livello costante corpo in acciaio e vaso in vetro.
Constant level oiler with steel body and glass bottle.

Ø vaso mm Ø bottle mm	capacità ml. capacity ml.	h. tot. mm h. tot. mm
61	120	92


Attacco: G1/4
Connection: BSP 1/4
Temperatura max. 100° C
Max. temperature 100° C
Peso Kg. 0,265
Weight Kg. 0,265



Art. 713

Oliatore con caricamento superiore del serbatoio.
Oiler with upper filling.

Ø vaso mm Ø bottle mm	capacità ml. capacity ml.	A	C	D
		A	C	D
40	40	70	40	8
50	90	88	50	8



Attacco: G1/4
Connection: BSP 1/4
Temperatura -20 +80°C
Temperature -20 +80°C
Materiale: ottone e plexiglass
Material: nickel plated brass and plexiglass

