

RUBINETTI RAPIDI UNIVERSALI UNIVERSAL QUICK COUPLINGS

Serie universale DN 7,5 • Universal type DN 7,5

DATI TECNICI

Fluidi compatibili	aria compressa
Corpo	ottone e acciaio
Guarnizione	NBR
Filettatura	cilindrica ISO 228
Temperatura di esercizio	-15 °C +80 °C
Pressione	max. 12 bar
Portata lt./min. a 6 bar	1000

TECHNICAL SPECIFICATIONS

Fluid	compressed air
Body	brass and steel
Seal	NBR
Thread	parallel ISO 228
Operating temperature	-15 °C +80 °C
Max. pressure	12 bar
Flow rate a 6 bar lt./min.	1000


ITALIAN PROFILE

GERMAN PROFILE


AMERICAN PROFILE

SWISS PROFILE


I dati tecnici e le quote non sono vincolanti • Drawings and specifications are not binding


Codice 6391
Rubinetto rapido universale maschio
Universal male quick coupler

A	C	⚙️	Profilo
1/4	52	19	Universale
3/8	52	19	Universale
1/2	56	22	Universale


Codice 6401
Rubinetto rapido universale femmina
Universal female quick coupler


A	C	⚙️	Profilo
1/4	52	19	Universale
3/8	55	19	Universale
1/2	55	25	Universale



Rubinetti rapidi universali • Universal quick couplings


Codice 6403
Rubinetto rapido universale portagomma
Universal quick coupler for rubber hose

T	C	⚙️	Profilo
6x10	71	19	Universale
6x14	71	19	Universale
8x12	71	19	Universale
8x13	71	19	Universale
8x15	71	19	Universale
8x17	71	19	Universale
10x15	76	19	Universale
10x17	76	19	Universale
10x19	76	19	Universale


Codice 8551
Rubinetto rapido universale per tubo spirale
Universal quick coupler for spiral hose

T	⚙️	Profilo
6x4	19	Universale
8x5	19	Universale
8x6	19	Universale
10x6,5	19	Universale
10x8	19	Universale
12x8	19	Universale
12x10	19	Universale

