



**Codice 6915** Raccordo girevole cilindrico  
Parallel orienting fitting

Pressione max. 15 bar  
Max. pressure 15 bar

A	B	L	1	2
1/8	6	24,5	13	13
1/4	8	31	16	16
3/8	9	34,5	20	18



**Codice 8521** Raccordo girevole a L  
Swivel female elbow

Pressione max. 15 bar  
Max. pressure 15 bar

F	F1	L	H	I
1/4	1/4	25	31,5	8



**Codice 6925** Raccordo di attraversamento  
Bulkhead connector

A	B	C max.	D	1	2
1/8	16x1,5	10	14	22	19
1/4	20x1,5	16	21	27	24
3/8	26x1,5	15	21	32	30
1/2	28x1,5	21	27	36	32



**Codice 6907** Tappo cilindrico  
Parallel plug

A	B	L	1
1/8	6	11	12
1/4	7	13	14
3/8	8	14	19
1/2	10	16	24
3/4	11	18	30
1"	12	20	36



**Codice 6913** Tappo cilindrico a scomparsa  
Parallel male plug

A	B	1
1/8	8	5
1/4	11	6
3/8	12,5	8
1/2	14	10



**Codice 6914** Tappo conico  
Tape plug

A	B	1
1/8	7,5	5
1/4	10	6
3/8	11	8
1/2	13	10



**Codice 6911** Tappo cilindrico a brugola con OR  
Parallel plug with hexagon embedded and O-ring

A	B	L	D	1
M5	4	6	8	2
8x1	5,4	8	12	4
10x1	6	8,5	14	5
1/8	6	8,5	14	5
1/4	8	11	17	6
3/8	9	12,5	20	8
1/2	10	13,5	25	10



**Codice 6916** Tappo cilindrico DIN 908 in acciaio zincato  
Parallel steel plug DIN 908

d	i	D	s	l
1/8	8	14	5	11
1/4	12	18	6	15
3/8	12	22	8	15
1/2	14	26	10	18
3/4	16	32	12	20
1	16	39	17	21



**Codice 6928** Tappo femmina  
Female plug

A	B	L	1
1/8	7,5	11	12
1/4	11	19	14
3/8	11,5	20	17
1/2	14	22	19



**Codice 6870** Raccordo a L maschio-femmina  
Male-female elbow

A	B	B1	C	L	CH
1/8	7,5	8,5	21	18	11
1/4	11	11	25,5	24	13
3/8	11,5	12	28	27	17
1/2	14	15	32	29,5	20
3/4	14,5	16,5	36,5	32	27
1"	16	19	45	39	30