

POMPA PNEUMATICA PER GRASSO ABNOX ABNOX AIR OPERATED GREASE PUMP

Pompa pneumatica per grasso • *Air operated grease pump*



per fusti/for drum Kg. 20/25

Art. 2070

per fusti/for drum Kg. 50

Art. 2072

per fusti/for drum Kg. 50-60

Art. 2073

per fusti/for drum Kg. 200

Art. 2074

Dati tecnici

Technical specifications

	Art. 2070	Art. 2072	Art. 2073	Art. 2074
Rapp. compressione <i>Pressure ratio</i>	60:1	60:1	60:1	60:1
Press. esercizio BAR min.-max. <i>Work pressure BAR min.-max.</i>	2 - 8	2 - 8	2 - 8	2 - 8
Pressione a 6 BAR <i>Pressure at 6 BAR</i>	335	335	335	335
Portata al colpo cm ³ <i>Output cm³ per stroke</i>	7,5	7,5	7,5	7,5
Uscita grasso s/tubo cm ³ min. <i>Output without hose cm³</i>	500	500	500	500
Consumo aria lt/min. <i>Air amount lt/min.</i>	150	150	150	150
Attacco <i>Connection</i>	G 1/4"	G 1/4"	G 1/4"	G 1/4"
Lunghezza pompante mm <i>Suction tube length mm</i>	370	473	720	845
Diametro pompante mm <i>Suction tube diam. mm</i>	32	32	32	32

