

SISTEMI DI DISTRIBUZIONE PER ARIA COMPRESSA DISTRIBUTION SYSTEM FOR COMPRESSED AIR


DATI TECNICI

| | |
|--------------------|---|
| Fluidi compatibili | aria compressa, vuoto e gas inerti (azoto, argon, ecc.) |
| Verniciatura | elettrostatica blu |
| Temperatura | min.-max. -20 °C +80 °C |
| Raccordi | ottone nichelato |
| Pressione | max. 16 bar |
| Filettature | gas conica ISO 7.1 gas cilindrica ISO 228 |

TECHNICAL SPECIFICATION

| | |
|---------------|---|
| Fluids | compressed air, vacuum and inert gas (azote, argon, etc.) |
| Painting | electrostatic blue |
| Temperature | min.-max. -20 °C +80 °C |
| Connection | nickel plated brass |
| Max. pressure | 16 bar |
| Threads | taper ISO 7.1 parallel ISO 228 |

I dati tecnici e le quote non sono vincolanti • Drawings and specifications are not binding



Codice 9001


Tubi in alluminio calibrato
Calibrated aluminium tubes

| Ø Esterno mm. Ø Outside mm. | Spess. mm. Thickness mm. | Pressione bar Pressure bar | Peso gr. Weight kg. | Lunghezza mt. Length mt. |
|--------------------------------|-----------------------------|-------------------------------|------------------------|-----------------------------|
| 20 | 1,5 | 15 | 235 | 4 |
| 25 | 1,5 | 15 | 298 | 4 |
| 32 | 1,5 | 15 | 387 | 4 |
| 40 | 1,5 | 15 | 490 | 4 |
| 50 | 2 | 15 | 814 | 4 |

Codice 9010

Raccordo diritto maschio
Straight male adaptor

| Tubo mm. Tube mm. | F | A | L | 1 | 2 |
|----------------------|--------|------|------|----|----|
| 20 | 1/2 | 14 | 56 | 22 | 30 |
| 25 | 3/4 | 16,5 | 66 | 27 | 35 |
| 32 | 1" | 19 | 76,5 | 34 | 45 |
| 40 | 1-1/4" | 21,5 | 89,5 | 45 | 55 |
| 50 | 1-1/2" | 21,5 | 105 | 50 | 65 |




Sistemi di distribuzione per aria compressa • Distribution system for compressed air



Codice 9005

Raccordo diritto femmina
Straight female adaptor


| Tubo mm. Tube mm. | F | A | L | 1 | 2 |
|----------------------|--------|------|------|----|----|
| 20 | 1/2 | 15 | 49 | 24 | 30 |
| 25 | 3/4 | 16,5 | 56,5 | 32 | 35 |
| 32 | 1" | 19 | 66,5 | 38 | 45 |
| 40 | 1-1/4" | 22 | 76 | 50 | 55 |
| 50 | 1-1/2" | 22 | 85,5 | 55 | 65 |



Codice 9020

Raccordo diritto intermedio
Straight connector


| Tubo mm. Tube mm. | L | 1 | 2 |
|----------------------|-------|----|----|
| 20 | 76,5 | 21 | 30 |
| 25 | 90,5 | 26 | 35 |
| 32 | 106,5 | 32 | 45 |
| 40 | 125 | 41 | 55 |
| 50 | 148,5 | 50 | 65 |



Codice 9015

Raccordo a L intermedio
Elbow connector

| Tubo mm. Tube mm. | L | 1 | 2 |
|----------------------|------|----|----|
| 20 | 51 | 21 | 30 |
| 25 | 61,5 | 26 | 35 |
| 32 | 74,5 | 34 | 45 |
| 40 | 86,5 | 41 | 55 |
| 50 | 104 | 50 | 65 |



Codice 9075

Raccordo a L maschio
Elbow male connector

| Tubo mm. Tube mm. | F | A | L | L1 | 2 |
|----------------------|--------|------|------|----|----|
| 20 | 1/2 | 14 | 51 | 32 | 30 |
| 25 | 3/4 | 16,5 | 61,5 | 37 | 35 |
| 32 | 1" | 19 | 74,5 | 49 | 45 |
| 40 | 1-1/4" | 21,5 | 86,5 | 54 | 55 |
| 50 | 1-1/2" | 21,5 | 104 | 59 | 65 |

